

SF 418 SE

Digitaler KABEL-RECEIVER

Digitaler Kabel-Receiver (DVB-C SD) mit eingebautem CONAX Kartenleser
USB 2.0 Anschluss (MP3 Player & JPEG Viewer)
HDMI Ausgang (576i) / Scart TV Ausgang



www.octagon-germany.de

Main Features

- * Digitaler Kabel-Receiver DVB-C SD
- * Conax Kartenleser
- * Software- Update Funktion über USB & RS-232C
- * USB 2.0 Anschluss (MP3 Player & JPEG Viewer)
- * HDMI Ausgang (576i)
- * MPEG-II Digital & Voll DVB-C (SD) kompatibel
- * EPG (Elektronischer Programmführer) Funktion
- * Hochauflösendes OSD Oberfläche
- * Favoriten- Gruppen für TV und Radio
- * Kanalsortierungsfunktionen nach Alphabet, Transponder und CAS
- * Kanalsortierungsfunktionen wie löschen, umbenennen, verschieben, sperren
- * OSD in verschiedenen Sprachen
- * Teletext und Untertitel Unterstützung
- * 10.000 Programmplätze für TV & Radio
- * Multipicture Funktion
- * Kindersicherung
- * FBAS, RGB und Audio über SCART (TV)
- * Abmessungen (L x B x T) 220mm x 35mm x 145mm

* Tuner & Channel Decoder

Input Connector	DIN-JACK ,IEC-169-2 FEMALE
Loop through out	DIN-JACK ,IEC-169-2 MALE
Frequency Range	50MHz ~ 1000MHz
Input Impedance	75Ω, unbalanced
Demodulation	QAM
Input Symbol Rate	1 ~ 7 Msp/s (for Annex A/C, BW 8MHz) 5.057 Msps(for 64QAM, Annex B) 5.361 Msps(for 256QAM, Annex B)
IF Bandwidth	6, 8 MHz(for Annex A/C) 6 MHz(for Annex B)
Modulation Format	16, 32, 64, 128, 256 QAM(for Annex A/C) 64, 256 QAM(for Annex B)

* MPEG Transport Stream A/V Decoding

Transport Stream	MPEG-II ISO/IEC 13818
Profile Level	MPEG-II MP@ML
Input Rate	Max. 15Mbit/s
Video Formats	4:3 LetterBox, 4:3 PanScan, 16:9
Video Resolution	720 x 576, 720 x 480
Audio Decoding	MPEG/MusiCam Layer I & II
Audio Mode	Stereo/Joint stereo/Mono
Sampling Rate	16, 22.05, 24, 32, 44.1KHz and 48KHz

* Main System

Main Processor	Trident Virgo Ultra
Memory	Flash-ROM : 2 MBytes SDRAM : 32 MBytes

* Audio / Video & Data IN/OUT

HDMI	576i Only
TV SCART	RGB, CVBS Video, Audio L, R Output
RS-232C	9 pin D-SUB (Male) type, Transfer rate 115Kbps
USB	USB 2.0 Host Support (5 V DC 500 mA Max)

* Front Panel

Slot	1 USB 2.0 Host Slot 1 Smart Cart Slot
Buttons	3 Buttons(Standby, CH UP/DOWN)
Display	NONE
Indicators	1 LEDs(Standby, Power and Remote: DUAL TYPE)

* Power Supply

Input Voltage	AC 100 ~ 250V, 50/60Hz
Type	SMPS
Power Consumption	Max. 15W
Standby Power	Max. 6W
Protection	Separate Internal Fuse & Lighting protection

* Physical Specification

Size (W x H x D)	220mm X 35mm X 145mm
Weight (Net)	0.7 Kg
Operating Temp.	0°C ~ +45°C
Storage Temp.	-10°C ~ +70°C

